


UNIVERSITÉ DE NANTES Estradas de Portugal, S.A.

ACCESSIBILITY & TRANSPORTS
Project nr 2008-1/049




duratiNet

7th Trans-national Workshop

Lisboa • LNEC • 30th May 2012


Maintenance Optimization and Decision Tools for Infrastructures in Atlantic Area

**Franck Schoefs, LUNAM Université, U. of Nantes, France
and all the partners of WG2 (TCD, U. Bordeaux, EP)**



European Union
European Regional
Development Fund

Investing in our common future



ATLANTIC AREA
Transnational Programme

duratiNet


7th Trans-national Workshop
Lisboa • LNEC • 30th May 2012


UNIVERSITÉ DE NANTES


Problem Definition

For a given structure how do we decide upon the optimal maintenance strategy as a function of age, condition, importance, required remaining life etc. in a robust/repeatable manner, avoiding generalisation/excessive conservatism such that our maintenance budget is optimised???

e.g. *Storstroem 1937, 3.2km*












ATLANTIC AREA
Transnational Programme


Investing in our common future




European Union
European Regional
Development Fund







7th Trans-national Workshop
Lisboa • LNEC • 30th May 2012



Some technical aspects


Statistical Modelling of:


- Loads
- Resistances
- Uncertainties
- Updating based upon results of tests/inspections

Purpose:


Cut strengthening or rehabilitation costs without compromising the safety level


Essentially a Bridge specific “code” is obtained






Investing in our common future






7th Trans-national Workshop
Lisboa • LNEC • 30th May 2012



Probability Based Maintenance Optimisation


Legal Basis – Eurocode 1 Basis of Design

Safety Level NEVER Compromised – Rather Optimised




3.5 Limit state design

- (1)P Design for limit states shall be based on the use of structural and load models for relevant limit states.
- (2)P It shall be verified that no limit state is exceeded when relevant design values for
 - actions,
 - material properties, or
 - product properties, and
 - geometrical data
 are used in these models.
- (3)P The verifications shall be carried out for all relevant design situations and load cases.
- (4) The requirements of 3.5(1)P should be achieved by the partial factor method, described in section 6.
- (5) As an alternative, a design directly based on probabilistic methods may be used.
- NOTE 1 The relevant authority can give specific conditions for use.
- NOTE 2 For a basis of probabilistic methods, see Annex C.
- (6)P The selected design situations shall be considered and critical load cases identified.
- (7) For a particular verification load cases should be selected, identifying compatible load arrangements, sets of deformations and imperfections that should be considered simultaneously with fixed variable actions and permanent actions.
- (8)P Possible deviations from the assumed directions or positions of actions shall be taken into account.
- (9) Structural and load models can be either physical models or mathematical models.



Investing in our common future



duratiNet

7th Trans-national Workshop
Lisboa • LNEC • 30th May 2012

UNIVERSITÉ DE NANTES

Few Examples

from

Portugal,

Ireland,

France

ATLANTIC AREA
Transnational Programme

Investing in our common future

European Union
European Regional Development Fund

duratiNet


LNEC
LABORATÓRIO NACIONAL DE ENGENHARIA CIVIL

7th Trans-
national Workshop

ATLANTIC AREA
Transnational Programme

UNIVERSITÉ DE NANTES

Ferrycarrig Bridge




Alternative Repair Options

Crosshead 1,7: Cem 1 OPC, 50mm cover
Crosshead 2: Cem 1 OPC, 70mm cover
Crosshead 3: Cem 1 OPC, silane surface treatment
Crosshead 4,6: Cem 1 OPC, 60% GGBS
Crosshead 5: Cem 1 OPC, mixed in corrosion inhibitors

Probabilistic Assessment

Torsional Capacity of Crosshead Beams



- Failed in Deterministic Assessment
- Passed in Probabilistic Assessment




ATLANTIC AREA
Transnational Programme


Investing in our common future

European Union
European Regional Development Fund







Economic Implications








Trans-r
Lis



ATLANTIC AREA
Transnational Programme




UNIVERSITÉ DE NANTES


Bridge	Conventional Approach	Probabilistic Approach	Saving
Vilsund	Max = 40 t	Max = 100 t	€3.2 m.
Skovdiget	Life = 0	Life > 10 yrs	€12 m.
Storstroem	Life = 0	Max = 100 t	€16 m.
Klovtofte	Max = 50 t	Max = 150 t	€1.6 m.
407-0028	Max = 60 t	Max = 100 t	€1.2 m.
30-0124	Max = 45 t	Max = 100 t	€0.4 m.
Norreso	Max = 50 t	Max = 100 t	€0.4 m.
Rodbyhavn	Max = 70 t	Max = 100 t	€0.4 m.
3 Sisters	Max = 80 t	Max = 100 t	€5.2 m.
			€40.4 m.

O' Connor, A. & Enevoldsen, I. (2007). 'Probability based Bridge Assessment'. ICE Journal of Bridge Engineering, Vol 160, No. 3, pp. 129-137.



ATLANTIC AREA
Transnational Programme

Investing in our common future



European Union
European Regional Development Fund



7th Trans-national Workshop
 Lisboa • LNEC • 30th May 2012



UNIVERSITÉ DE NANTES

Thank you for your attention





ATLANTIC AREA
Transnational Programme

Investing in our common future



European Union
European Regional Development Fund